

(19) World Intellectual Property
Organization
International Bureau



23 MAR 2005

(43) International Publication Date
8 April 2004 (08.04.2004)


PCT

(10) International Publication Number
WO 2004/028927 A1

- (51) International Patent Classification⁷: B65D 85/10
- (21) International Application Number: PCT/IT2003/000572
- (22) International Filing Date: 25 September 2003 (25.09.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
BO2002A000606
26 September 2002 (26.09.2002) IT
- (71) Applicant (for all designated States except US): G.D. SOCIETA' PER AZIONI [IT/IT]; Via Battindamo, 91, I-40133 Bologna (IT).
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): GIANNINI, Antonella [IT/IT]; Via Murri, 114, I-40137 Bologna (IT). CREMONINI, Paolo [IT/IT]; Via Zambeccari, 20, I-40134 Bologna (IT).
- (74) Agents: JORIO, Paolo et al.; C/O Studio Torta S.r.L., Via Viotti, 9, 10121 Torino (IT).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (81) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),

[Continued on next page]

(54) Title: RIGID SIDE-OPEN PACKAGE FOR TOBACCO ARTICLES



(57) Abstract: A rigid package (1) for tobacco articles, having a container (3) with an open end (4), and a lid (5) hinged to the container (3) to rotate between an open position and a closed position respectively opening and closing the open end (4); when the lid (5) is in the closed position, the container (3) is substantially parallelepiped-shaped and has two, respectively top and bottom, end walls (7, 8); and a lateral surface bounded by the end walls (7, 8) and having two, respectively front and rear, major lateral walls (10, 11), and two minor lateral walls (9); four longitudinal edges (12) are defined between the major lateral walls (10, 11) and the minor lateral walls (9), and eight transverse edges (13) are defined between the lateral walls (9, 10, 11) and the end walls (7, 8); the lid (5) is hinged along a hinge (6) formed in the rear major lateral wall (11) and parallel to the longitudinal edges (12); and the lid (5) includes part of the end walls (7, 8), part of the major lateral walls (10, 11), and a minor lateral wall (9). The articles are retained in an inner container (14) slidingly received within the outer container.

WO 2004/028927 A1



European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

JC17 Rec'd PCT/PTO 23 MAR 2005

7/PRTS

5

RIGID SIDE-OPEN PACKAGE FOR TOBACCO ARTICLES

TECHNICAL FIELD

10 The present invention relates to a rigid package for tobacco articles.

 The present invention may be used to particular advantage in a rigid cigarette packet, to which the following description refers purely by way of example.

15

BACKGROUND ART

 A rigid cigarette packet normally comprises a cup-shaped bottom container having an open top end; and a cup-shaped top lid hinged to the container along a hinge
20 to rotate, with respect to the container, between an open position and a closed position respectively opening and closing the open end of the bottom container. When the lid is in the closed position, the packet is substantially parallelepiped-shaped, and comprises two,
25 respectively top and bottom, end walls, and a lateral surface bounded by the end walls and defined by two, respectively front and rear, major lateral walls, and two minor lateral walls. Four longitudinal edges are defined

between the minor lateral walls and the major lateral walls; eight transverse edges, smaller than the longitudinal edges, are defined between the lateral walls and the end walls; and the lid hinge is formed in the rear wall and parallel to the transverse edges defined between the rear wall and the end walls.

Rigid slide-open cigarette packets are also known, such as those described in Patent Application FR-2499947-A3, Patent US-4534463-A1, or Patent US-5080227-A1. A rigid slide-open cigarette packet comprises a first container for housing a group of cigarettes wrapped in a sheet of foil, and which in turn is housed inside a second container so as to slide with respect to the second container between an inserted position, in which the first container is fully inserted inside the second container, and an extracted position, in which part of the first container is extracted from the second container. Each container is substantially parallelepiped-shaped, and comprises two end walls; and a lateral surface bounded by the end walls and defined by lateral walls separated from one another by corresponding square longitudinal edges.

Though marketed, by being relatively easy to produce and generally popular with smokers, rigid cigarette packets of the above type fail to provide for effectively protecting the cigarettes inside the packet, in that, when the packet is carried in the user's pocket, both the lid of the hinged-lid packet and the inner container of

the slide-open packet tend to work open, thus resulting in fallout of the cigarettes.

DISCLOSURE OF THE INVENTION

5 It is an object of the present invention to provide a rigid package for tobacco articles, designed to eliminate the aforementioned drawbacks, and which, in particular, is cheap and easy to produce.

 According to the present invention, there is
10 provided a rigid package for tobacco articles; the package comprising a first container having an open end, and a lid hinged to the first container to rotate between an open position and a closed position respectively opening and closing the open end; when the lid is in the
15 closed position, the first container being substantially parallelepiped-shaped, and comprising two, respectively top and bottom, end walls, and a lateral surface bounded by the end walls and comprising two, respectively front and rear, major lateral walls, two minor lateral walls,
20 four longitudinal edges, each defined between a major lateral wall and a minor lateral wall, and eight transverse edges, each defined between an end wall and a lateral wall; the lid being hinged along a hinge formed in the rear wall and substantially parallel to the
25 longitudinal edges, and the lid comprising part of the end walls, part of the major lateral walls, and a minor lateral wall; and the package being characterized by comprising a second container for housing the tobacco

articles and which is housed in sliding manner inside the first container to slide, with respect to the first container, between an inserted position, in which the second container is fully inserted inside the first container, and an extracted position, in which part of the second container is extracted from the first container and projects from the open end of the first container.

According to the present invention, there is also provided a rigid package for tobacco articles; the package comprising a container having an open end, and a lid hinged to the container to rotate between an open position and a closed position respectively opening and closing the open end; when the lid is in the closed position, the container being substantially parallelepiped-shaped, and comprising two, respectively top and bottom, end walls, and a lateral surface bounded by the end walls and comprising two, respectively front and rear, major lateral walls, two minor lateral walls, four longitudinal edges, each defined between a major lateral wall and a minor lateral wall, and eight transverse edges, each defined between an end wall and a lateral wall; the lid being hinged along a hinge formed in the rear wall and substantially parallel to the longitudinal edges, and the lid comprising part of the end walls, part of the major lateral walls, and a minor lateral wall; and the container having a collar, which projects partly from the open end, defines a withdrawal

opening for the tobacco articles, at least at the top end wall of the container, and engages a corresponding inner surface of the lid when the lid is in the closed position; the package being characterized in that, when
5 the lid is in the closed position, at least at the front wall, an edge of the lid is detached from an edge of the container to partly expose the portion of the underlying collar projecting from the open end.

10 BRIEF DESCRIPTION OF THE DRAWINGS

A number of non-limiting embodiments of the present invention will be described by way of example with reference to the accompanying drawings, in which:

Figure 1 shows a front view in perspective of a
15 preferred embodiment of a rigid cigarette packet in accordance with the present invention and in a closed configuration;

Figure 2 shows a front view in perspective of the Figure 1 rigid cigarette packet in an open configuration;

20 Figure 3 shows an exploded view in perspective of the Figure 1 rigid cigarette packet;

Figure 4 shows a plan view of a blank by which to produce an inner container of the rigid cigarette packet in Figures 1 to 3;

25 Figure 5 shows a plan view of a blank by which to produce an outer container of the rigid cigarette packet in Figures 1 to 3;

Figure 6 shows a front view in perspective of an

alternative embodiment of a rigid cigarette packet in accordance with the present invention and in a closed configuration;

Figure 7 shows a front view in perspective of the
5 Figure 6 rigid cigarette packet in an open configuration;

Figure 8 shows a plan view of a blank by which to produce the container of the rigid cigarette packet in Figures 6 and 7;

Figures 9 and 10 show front views in perspective of
10 two variations of the rigid cigarette packet in Figures 6 and 7.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Number 1 in the accompanying drawings indicates as a
15 whole a rigid cigarette packet for housing an orderly group 2 of cigarettes wrapped in a sheet of foil, and which comprises a cup-shaped container 3 having an open end 4. A cup-shaped lid 5 is connected to container 3 and hinged to container 3 along a hinge 6 (shown in Figures 3
20 and 5) to rotate, with respect to container 3, between an open position (Figure 2) and a closed position (Figure 1) respectively opening and closing open end 4.

When lid 5 is in the closed position, container 3 is in the form of a substantially rectangular parallelepiped
25 comprising a lateral surface; and two identical, flat, respectively top and bottom, end walls 7 and 8 facing and parallel to each other and bounding the lateral surface. The lateral surface of container 3 comprises two flat,

facing, parallel minor lateral walls 9, and two flat, facing major lateral walls 10 and 11 crosswise to minor lateral walls 9. More specifically, one major lateral wall 10 defines a front wall of container 3, and the
5 other major lateral wall 11 defines a rear wall of container 3.

Four longitudinal edges 12 are defined between minor lateral walls 9 and major lateral walls 10, 11; and eight transverse edges 13 are defined between end walls 7, 8
10 and lateral walls 9, 10, 11, are crosswise to longitudinal edges 12, and are divided into major transverse edges 13 defined between end walls 7, 8 and major lateral walls 10, 11, and minor transverse edges 13 defined between end walls 7, 8 and minor lateral walls 9.

15 More specifically, hinge 6 is formed in rear major lateral wall 11, and is parallel to longitudinal edges 12 of container 3, so that lid 5 comprises part of end walls 7, 8, part of major lateral walls 10, 11, and a minor lateral wall 9 of container 3.

20 A further container 14, housing group 2 of cigarettes, is housed in sliding manner inside container 3, and slides with respect to container 3 between an inserted position (Figure 1), in which container 14 is fully inserted inside container 3, and an extracted
25 position (Figure 2), in which part of container 14 is extracted from container 3 and projects from open end 4 of container 3.

Container 14 is parallelepiped-shaped, and comprises

a top end wall 15; a bottom end wall 16; and a lateral surface bounded by end walls 15 and 16, and which comprises two opposite, parallel major lateral walls 17, and two opposite, parallel minor lateral walls 18 separated from major lateral walls 17 by four longitudinal edges 19. Lateral walls 17 and 18 of container 14 are separated from end walls 15 and 16 by eight transverse edges 20, which are divided into four major transverse edges 20 between major lateral walls 17 and end walls 15 and 16, and four minor transverse edges 20 between minor lateral walls 18 and end walls 15 and 16.

Top end wall 15 of container 14 comprises an open portion 21, which also extends along part of major lateral walls 17, and permits removal of the cigarettes from container 14 when container 14 is in said extracted position (Figure 2). More specifically, the cigarettes in group 2 of cigarettes inside container 14 are arranged parallel to longitudinal edges 19 of container 14, and therefore parallel to longitudinal edges 12 of container 3.

Longitudinal edges 19 of container 14 are rounded edges, i.e. each edge 19 is defined by a quarter of a cylindrical surface to connect respective lateral walls 17 and 18 with a constant radius of curvature (preferably slightly larger than the radius of a cigarette); and transverse edges 20 of container 14 and all the edges 12 and 13 of container 3 are sharp square edges. In a

different embodiment not shown, longitudinal edges 12 of container 3 are also rounded edges. In a further embodiment not shown, some transverse edges 13 of container 3 and/or some transverse edges 20 of container 14 may be rounded non-square edges, so that both transverse edges 13 and/or 20 and longitudinal edges 12 and/or 19 are rounded non-square edges.

In further embodiments not shown, all the edges 19 and 20 of container 14 and all the edges 12 and 13 of container 3 are sharp square edges, or some of edges 19 and 20 of container 14 and/or some of edges 12 and 13 of container 3 are rounded or bevelled non-square edges. Alternatively, at least one lateral wall 9, 10, 11, 17, 18 of at least one container 3, 14 has an outwardly convex profile, is connected to at least one relative lateral wall 9, 10, 11, 17, 18 along a sharp longitudinal edge 12, 19, and subtends with said lateral wall 9, 10, 11, 17, 18 a substantially obtuse dihedral angle; or at least one lateral wall 9, 10, 11, 17, 18 of at least one container 3, 14 has an outwardly convex profile, is connected to at least one relative end wall 7, 8, 15, 16 along a sharp transverse edge 13, 20, and subtends with end wall 7, 8, 15, 16 a substantially obtuse dihedral angle.

By way of example, the embodiments described above may substantially reproduce the form of the cigarette packets described in Patent Applications EP-A1-1066206, IT-BO01A000584 or EP-A1-0764595.

When container 14 is in said inserted position (Figure 1), each lateral wall 17, 18 of container 14 obviously faces and is aligned with a corresponding lateral wall 10, 11, 9 of container 3. More specifically, both containers 14 and 3 are sized to house group 2 of cigarettes and container 14 respectively with a small amount of clearance, thus minimizing the amount of packing material required to produce containers 3 and 14, and also minimizing movement of group 2 of cigarettes inside container 14, and of container 14 inside container 3. Obviously, a certain amount of clearance must be allowed between group 2 of cigarettes and container 14, and between container 14 and container 3, to permit easy withdrawal by the user of the cigarettes from container 14, and of container 14 from container 3 respectively.

A minor lateral wall 9 of container 3 has a hole 22 (Figure 3) shaped and sized to permit insertion of the user's finger, and which provides for assisting expulsion of container 14 from container 3, by the user applying pressure on the minor lateral wall 18 of container 14 facing hole 22 when container 14 is in said inserted position (Figure 1).

In an embodiment not shown, packet 1 comprises stop means for limiting slide of container 14 with respect to container 3, and so preventing detachment of container 14 from container 3; which stop means are defined by two tongues projecting from major lateral walls 17 of container 14, and by two tongues projecting from major

lateral walls 10 and 11 of container 3. Each tongue of container 14 projects outwards of container 14 from a respective major lateral wall 17; each tongue of container 3 projects inwards of container 3 from a
5 respective major lateral wall 10, 11, and is located close to open end 4 of container 3; and each tongue of container 3 is so located as to engage the corresponding tongue of container 14 as container 14 slides out of container 3, thus preventing detachment of container 14
10 from container 3.

In accordance with an embodiment not shown, when lid 5 is in the closed position, at front major lateral wall 10 of container 3, an edge 31 of lid 5 is detached from an edge 31 of container 3 to partly expose the underlying
15 container 14.

As shown in Figure 4, container 14 is formed from a corresponding flat blank 23, which is substantially in the form of an elongated rectangle, and the component parts of which are indicated, where possible, using the
20 same reference numbers, with superscripts, as for the corresponding parts of container 14.

Blank 23 comprises two groups 24 of longitudinal crease lines 25, and a number of transverse crease lines 26 defining, between the two groups 24 of longitudinal
25 crease lines 25, a panel 15' forming part of top end wall 15; a panel 17' forming one major lateral wall 17; a panel 16' forming bottom end wall 16; a panel 17" forming the other major lateral wall 17; and a panel 15" forming

part of top end wall 15. Panel 17' comprises two wings 18', which are located on opposite sides of panel 17', are separated from panel 17' by the two groups 24 of longitudinal crease lines 25, and form respective outer portions of minor lateral walls 18; and panel 17" comprises two wings 18", which are located on opposite sides of panel 17", are separated from panel 17" by the two groups 24 of longitudinal crease lines 25, and form respective inner portions of minor lateral walls 18. Wings 18" are connected to a further two wings 16", which form respective inner portions of bottom end wall 16; and each group 24 of longitudinal crease lines 25 comprises a number of longitudinal crease lines 25, and forms two rounded longitudinal edges 19 of container 14.

As shown in Figure 5, container 3 is formed from a corresponding flat blank 27, which is substantially rectangular, and the component parts of which are indicated, where possible, using the same reference numbers, with superscripts, as for the corresponding parts of container 3.

Blank 27 comprises two longitudinal crease lines 28, and a number of transverse crease lines 29 defining, between the two longitudinal crease lines 28, a panel 10' forming part of front major lateral wall 10; a panel 9' forming one minor lateral wall 9; a panel 11' forming the rear major lateral wall 11; a panel 9" forming the other minor lateral wall 9; and a panel 10" forming the rest of front major lateral wall 10. Panels 10', 11', 10" have

respective pairs of wings 7' and 8', which are located on opposite sides of panels 10', 11', 10", are separated from panels 10', 11', 10" by longitudinal crease lines 28, and form end walls 7, 8. Each wing 7', 8' of panel 5 11' has two wings 9'''', which are located at opposite ends of wing 7', 8', are separated from wing 7', 8' by transverse crease lines 29, and form respective inner portions of minor lateral walls 9.

In the alternative embodiment shown in Figures 6 and 10 7, packet 1 only comprises container 3, in which group 2 of cigarettes is housed. More specifically, container 3 comprises a collar 30 projecting partly from open end 4, and which engages a corresponding inner surface of lid 5 when lid 5 is in the closed position. More specifically, 15 the collar 30 in Figure 7 has rounded exposed longitudinal edges. Alternatively, the exposed longitudinal edges of collar 30 may be bevelled or square. More specifically, the cigarettes in group 2 of cigarettes inside container 3 are parallel to 20 longitudinal edges 12 of container 3, and collar 30 defines a cigarette withdrawal opening at top end wall 7, front major lateral wall 10, and a minor lateral wall 9.

When lid 5 is in the closed position, at front major lateral wall 10, an edge 31 of lid 5 is detached from an 25 edge 31 of container 3 to partly expose the portion of the underlying collar 30 projecting from open end 4. Along front major lateral wall 10 of container 3, the edge 31 of lid 5 is parallel to the edge 31 of container

3, so that the distance between edge 31 of lid 5 and edge 31 of container 3 is constant. Moreover, when lid 5 is in the closed position, at end walls 7 and 8, edge 31 of lid 5 substantially contacts edge 31 of container 3.

5 In the alternative embodiments shown in Figures 9 and 10, along front major lateral wall 10 of container 3, the distance between the edge 31 of lid 5 and the edge 31 of container 3 varies. As shown in Figures 6, 7, 9, 10, the edge 31 of lid 5 and the edge 31 of container 3 may
10 obviously be defined by a straight line (Figures 6 and 7), by a bent line (Figure 10), or by a curved line (Figure 9).

As shown in Figure 8, container 3 in Figures 6 and 7 is formed from a corresponding flat blank 27, which is
15 substantially rectangular, and the component parts of which are indicated, where possible, using the same reference numbers, with superscripts, as for the corresponding parts of container 3.

Blank 27 comprises two longitudinal crease lines 28,
20 and a number of transverse crease lines 29 defining, between the two longitudinal crease lines 28, a panel 10' forming part of front major lateral wall 10; a panel 9' forming one minor lateral wall 9; a panel 11' forming the rear major lateral wall 11; a panel 9" forming the other
25 minor lateral wall 9; and a panel 10" forming the rest of front major lateral wall 10. Panels 10', 11', 10" have respective pairs of wings 7' and 8', which are located on opposite sides of panels 10', 11', 10", are separated

from panels 10', 11', 10" by longitudinal crease lines 28, and form end walls 7, 8. Each wing 7', 8' of panel 11' has two wings 9''', which are located at opposite ends of wing 7', 8', are separated from wing 7', 8' by transverse crease lines 29, and form respective inner portions of minor lateral walls 9.

Tests have shown that the anatomical shape of cigarette packets 1 as described above provides for easy handling by the user. Moreover, the fact that lid 5 is located to the side of container 3 (comprising part of end walls 7, 8, part of major lateral walls 10, 11, and a minor lateral wall 9) safeguards against accidental opening of lid 5 when packet 1 is in the user's pocket, thus effectively protecting the cigarettes inside packet 1.

Given the numerous advantages of cigarette packets 1 as described above, the form of packets 1 may also be applied completely to the manufacture of other types of rigid containers for tobacco articles, such as cartons of packets of cigarettes, or cigar packets.

CLAIMS

1) A rigid package for tobacco articles; the package (1) comprising a first container (3) having an open end (4), and a lid (5) hinged to the first container (3) to rotate between an open position and a closed position respectively opening and closing the open end (4); when the lid (5) is in the closed position, the first container (3) being substantially parallelepiped-shaped, and comprising two, respectively top and bottom, end walls (7, 8), and a lateral surface bounded by the end walls (7, 8) and comprising two, respectively front and rear, major lateral walls (10, 11), two minor lateral walls (9), four longitudinal edges (12), each defined between a major lateral wall (10; 11) and a minor lateral wall (9), and eight transverse edges (13), each defined between an end wall (7; 8) and a lateral wall (9; 10; 11); the lid (5) being hinged along a hinge (6) formed in the rear major lateral wall (11) and substantially parallel to the longitudinal edges (12), and the lid (5) comprising part of the end walls (7, 8), part of the major lateral walls (10, 11), and a minor lateral wall (9); and the package (1) being characterized by comprising a second container (14) for housing the tobacco articles (2) and which is housed in sliding manner inside the first container (3) to slide, with respect to the first container (3), between an inserted position, in which the second container (14) is fully

inserted inside the first container (3), and an extracted position, in which part of the second container (14) is extracted from the first container (3) and projects from the open end (4) of the first container (3).

5 2) A package as claimed in Claim 1, characterized in that, when the lid (5) is in the closed position, at least at the front major lateral wall (10), an edge (31) of the lid (5) is detached from an edge (32) of the first container (3) to partly expose the underlying second
10 container (14).

 3) A package as claimed in Claim 2, characterized in that, along the front major lateral wall (10) of the first container (3), the edge (31) of the lid (5) is parallel to the edge (32) of the first container (3), so
15 that the distance between the edge (31) of the lid (5) and the edge (32) of the first container (3) is constant.

 4) A package as claimed in Claim 2, characterized in that, along the front major lateral wall (10) of the first container (3), the distance between the edge (31)
20 of the lid (5) and the edge (32) of the first container (3) varies.

 5) A package as claimed in any one of Claims 2 to 4, characterized in that, when the lid (5) is in the closed position, at the end walls (7, 8), the edge (31) of the
25 lid (5) substantially contacts the edge (32) of the first container (3).

 6) A package as claimed in any one of Claims 2 to 5, characterized in that the edge (31) of the lid (5) and

the edge (32) of the first container (3) are defined by a straight line.

7) A package as claimed in any one of Claims 2 to 5, characterized in that the edge (31) of the lid (5) and
5 the edge (32) of the first container (3) are defined by a bent line.

8) A package as claimed in any one of Claims 2 to 5, characterized in that the edge (31) of the lid (5) and
the edge (32) of the first container (3) are defined by a
10 curved line.

9) A package as claimed in any one of Claims 1 to 8, characterized in that the second container (14) is substantially parallelepiped-shaped, and comprises two, respectively top and bottom, end walls (15, 16), and a
15 lateral surface bounded by the end walls (15, 16) and comprising two, respectively front and rear, major lateral walls (17), two minor lateral walls (18), four longitudinal edges (19), each defined between a major lateral wall (17) and a minor lateral wall (18), and
20 eight transverse edges (20), each defined between an end wall (15; 16) and a lateral wall (17; 18); the top end wall (15) of the second container (14) comprising an open portion (21) by which to extract the tobacco articles (2) from the second container (14) when the second container
25 (14) is in the extracted position.

10) A package as claimed in Claim 9, characterized in that the longitudinal edges (19) of the second container (14) are rounded edges.

11) A package as claimed in Claim 10, characterized in that the longitudinal edges (12) of the first container (3) are square edges.

12) A package as claimed in Claim 10, characterized
5 in that the longitudinal edges (12) of the first container (3) are rounded edges.

13) A package as claimed in any one of Claims 10 to 12, characterized in that the second container (14) is formed from a respective flat blank (23) comprising two
10 groups (24) of longitudinal crease lines (25), and a number of transverse crease lines (26) defining, between the two groups (24) of longitudinal crease lines (25), a first panel (15') forming part of the top end wall (15), a second panel (17') forming one major lateral wall (17),
15 a third panel (16') forming the bottom end wall (16), a fourth panel (17'') forming the other major lateral wall (17), and a fifth panel (15'') forming part of the top end wall (15); the second panel (17') comprising two first wings (18'), which are located on opposite sides of the
20 second panel (17'), are separated from the second panel (17') by the two groups (24) of longitudinal crease lines (25), and form respective portions of the minor lateral walls (18); the fourth panel (17'') comprising two second wings (18''), which are located on opposite sides of the
25 fourth panel (17''), are separated from the fourth panel (17'') by the two groups (24) of longitudinal crease lines (25), and form respective portions of the minor lateral walls (18); and each group (24) of longitudinal crease

lines (25) comprising a number of longitudinal crease lines (25).

14) A package as claimed in any one of Claims 1 to 13, characterized in that the first container (3) is formed from a respective flat blank (27) comprising two longitudinal crease lines (28), and a number of transverse crease lines (29) defining, between the two longitudinal crease lines (28), a first panel (10') forming part of the front major lateral wall (10), a second panel (9') forming one minor lateral wall (9), a third panel (11') forming the rear major lateral wall (11), a fourth panel (9'') forming the other minor lateral wall (9), and a fifth panel (10'') forming the rest of the front major lateral wall (10); the first, third and fifth panel (10', 11', 10'') having respective pairs of wings (7', 8'), which are located on opposite sides of the first/third/fifth panel (10', 11', 10''), are separated from the first/third/fifth panel (10', 11', 10'') by the longitudinal crease lines (28), and form the end walls (7, 8); each wing (7'; 8') of the third panel (11') having two wings (9'''), which are located at opposite ends of the wing (7'; 8'), are separated from the wing (7'; 8') by the transverse crease lines (29), and form respective inner portions of the minor lateral walls (9).

15) A package as claimed in Claim 9, characterized in that at least one edge (12; 13; 19; 20) of at least one of the containers (3; 14) is a non-square edge.

16) A package as claimed in Claim 15, characterized

in that at least one edge (12; 13; 19; 20) of at least one of the containers (3; 14) is a rounded non-square edge.

17) A package as claimed in Claim 15, characterized
5 in that at least one edge (12; 13; 19; 20) of at least one of the containers (3; 14) is a bevelled non-square edge.

18) A package as claimed in Claim 15, characterized
10 in that at least one lateral wall (9; 10; 11; 17; 18) of at least one container (3; 14) has an outwardly convex profile, is connected to at least one relative lateral wall (9; 10; 11; 17; 18) along a sharp longitudinal edge (12; 19), and subtends with the lateral wall (9; 10; 11; 17; 18) a substantially obtuse dihedral angle.

15 19) A package as claimed in Claim 15, characterized in that at least one lateral wall (9; 10; 11; 17; 18) of at least one container (3; 14) has an outwardly convex profile, is connected to at least one relative end wall (7; 8; 15; 16) along a sharp transverse edge (13; 20),
20 and subtends with the end wall (7; 8; 15; 16) a substantially obtuse dihedral angle.

20) A package as claimed in any one of Claims 1 to 19, characterized in that the minor lateral wall (9) of the first container (3) opposite the lid (5) comprises at
25 least one through hole (22) sized to permit insertion of a user's finger.

21) A package as claimed in any one of Claims 1 to 20, characterized by comprising stop means for limiting

slide of the second container (14) with respect to the first container (3), so as to prevent detachment of the second container (14) from the first container (3).

22) A package as claimed in Claim 21, characterized
5 in that the stop means comprise at least one first tongue projecting outwards of the second container (14) from a respective major lateral wall (17) of the second container (14), and a second tongue projecting inwards of
10 the first container (3) from a respective major lateral wall (10; 11) of the first container (3) and located close to the open end (4) of the first container (3); the first and second tongue being so located that the first tongue engages the second tongue as the second container (14) slides out of the first container (3).

15 23) A rigid package for tobacco articles; the package (1) comprising a container (3) having an open end (4), and a lid (5) hinged to the container (3) to rotate between an open position and a closed position respectively opening and closing the open end (4); when
20 the lid (5) is in the closed position, the container (3) being substantially parallelepiped-shaped, and comprising two, respectively top and bottom, end walls (7, 8), and a lateral surface bounded by the end walls (7, 8) and comprising two, respectively front and rear, major
25 lateral walls (10, 11), two minor lateral walls (9), four longitudinal edges (12), each defined between a major lateral wall (10; 11) and a minor lateral wall (9), and eight transverse edges (13), each defined between an end

wall (7; 8) and a lateral wall (9; 10; 11); the lid (5) being hinged along a hinge (6) formed in the rear major lateral wall (11) and substantially parallel to the longitudinal edges (12), and the lid (5) comprising part
5 of the end walls (7, 8), part of the major lateral walls (10, 11), and a minor lateral wall (9); and the container (3) having a collar (30), which projects partly from the open end (4), defines a withdrawal opening for the tobacco articles (2), at least at the top end wall (7) of
10 the container (3), and engages a corresponding inner surface of the lid (5) when the lid (5) is in the closed position; the package (1) being characterized in that, when the lid (5) is in the closed position, at least at the front major lateral wall (10), an edge (31) of the
15 lid (5) is detached from an edge (32) of the container (3) to partly expose the portion of the underlying collar (30) projecting from the open end (4).

24) A package as claimed in Claim 23, characterized in that, along the front major lateral wall (10) of the
20 container (3), the edge (31) of the lid (5) is parallel to the edge (32) of the container (3), so that the distance between the edge (31) of the lid (5) and the edge (32) of the container (3) is constant.

25) A package as claimed in Claim 23, characterized in that, along the front major lateral wall (10) of the
25 container (3), the distance between the edge (31) of the lid (5) and the edge (32) of the container (3) varies.

26) A package as claimed in any one of Claims 23 to

25, characterized in that, when the lid (5) is in the closed position, at the end walls (7, 8), the edge (31) of the lid (5) substantially contacts the edge (32) of the container (3).


5 27) A package as claimed in any one of Claims 23 to 26, characterized in that the edge (31) of the lid (5) and the edge (32) of the container (3) are defined by a straight line.


10 28) A package as claimed in any one of Claims 23 to 26, characterized in that the edge (31) of the lid (5) and the edge (32) of the container (3) are defined by a bent line.


15 29) A package as claimed in any one of Claims 23 to 26, characterized in that the edge (31) of the lid (5) and the edge (32) of the container (3) are defined by a curved line.

20 30) A package as claimed in any one of Claims 23 to 29, characterized in that the container (3) is formed from a respective flat blank (27) comprising two longitudinal crease lines (28), and a number of transverse crease lines (29) defining, between the two longitudinal crease lines (28), a first panel (10') forming part of the front major lateral wall (10), a second panel (9') forming one minor lateral wall (9), a third panel (11') forming the rear major lateral wall (11), a fourth panel (9'') forming the other minor lateral wall (9), and a fifth panel (10'') forming the rest of the front major lateral wall (10); the first, third and fifth

panel (10', 11', 10") having respective pairs of wings (7', 8'), which are located on opposite sides of the first/third/fifth panel (10', 11', 10"), are separated from the first/third/fifth panel (10', 11', 10") by the
5 longitudinal crease lines (28), and form the end walls (7, 8); each wing (7'; 8') of the third panel (11') having two wings (9'''), which are located at opposite ends of the wing (7'; 8'), are separated from the wing (7'; 8') by the transverse crease lines (29), and form
10 respective inner portions of the minor lateral walls (9).











Fig.5







Fig.8



INTERNATIONAL SEARCH REPORT

International Classification No
PCT/IT 03/00572

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 B65D85/10

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 6 360 943 B1 (FOCKE HEINZ ET AL) 26 March 2002 (2002-03-26) figures 1-3	23, 25, 26, 28, 30
X	WO 00/34150 A (FOCKE HEINZ ; BUSE HENRY (DE); FOCKE & CO (DE)) 15 June 2000 (2000-06-15) figures 12-14	23, 25, 26, 29, 30
X	WO 99/65796 A (FOCKE HEINZ ; BUSE HENRY (DE); FOCKE & CO (DE)) 23 December 1999 (1999-12-23) figures 1-3	23, 24, 26, 27, 30
E	WO 03/078274 A (BRITISH AMERICAN TOBACCO CO ; TEARLE ALAN DOUGLAS (GB); HOLFORD STEVEN) 25 September 2003 (2003-09-25) figures 3,4	23, 24, 27, 30
-/-		

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents :**

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

26 January 2004

Date of mailing of the international search report

02/02/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Bridault, A

INTERNATIONAL SEARCH REPORT

International Patent No.

PCT/IT 03/00572

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages.	Relevant to claim No.
A	US 6 435 342 B1 (AGNES HJARALD EDGAR) 20 August 2002 (2002-08-20) claim 1; figure 1	1,23
A	FR 2 499 947 A (REYNOLDS TOBACCO GMBH) 20 August 1982 (1982-08-20) cited in the application claims 1,4,6; figures	1,9,14, 20-22
A	FR 2 495 114 A (LECAM MARC) 4 June 1982 (1982-06-04) claim 1; figures 1-5	1

INTERNATIONAL SEARCH REPORT

International application No.
PCT/IT 03/00572

Box I Observations where certain claims were found unsearchable (Continuation of item 1 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☐ Claims Nos.:
because they relate to subject matter not required to be searched by this Authority, namely:
2. ☐ Claims Nos.:
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
3. ☐ Claims Nos.:
because they are dependent claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box II Observations where unity of invention is lacking (Continuation of item 2 of first sheet)

This International Searching Authority found multiple inventions in this International application, as follows:

see additional sheet

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☒ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

This International Searching Authority found multiple (groups of) inventions in this international application, as follows:

1. claims: 1-22

A package for tobacco products having an outer container with a hinged lid and an inner, sliding container.

2. claims: 23-30

A package for tobacco products having a container with a hinged lid and a collar.

INTERNATIONAL SEARCH REPORT

Information on patent family members

International

Location No

PCT/IT 03/00572

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 6360943	B1	26-03-2002	DE 19906473 A1 24-08-2000
			AU 765240 B2 11-09-2003
			AU 1864900 A 04-09-2000
			BG 105845 A 30-04-2002
			BR 9917134 A 22-01-2002
			CA 2371802 A1 24-08-2000
			CN 1125763 B 29-10-2003
			WO 0048926 A1 24-08-2000
			EP 1152961 A1 14-11-2001
			JP 2002537190 T 05-11-2002
			PL 350037 A1 21-10-2002
			TR 200102397 T2 21-01-2002
			ZA 200106747 A 15-11-2002
WO 0034150	A	15-06-2000	DE 19858786 A1 15-06-2000
			AU 1558000 A 26-06-2000
			BG 105594 A 31-01-2002
			BR 9916072 A 04-09-2001
			CA 2358414 A1 15-06-2000
			CN 1329567 T 02-01-2002
			WO 0034150 A1 15-06-2000
			EP 1281636 A2 05-02-2003
			EP 1140661 A1 10-10-2001
			ID 29808 A 11-10-2001
			JP 2002531349 T 24-09-2002
			PL 349342 A1 15-07-2002
			TR 200101662 T2 22-10-2001
			US D441496 S1 01-05-2001
			US D448888 S1 02-10-2001
			US 6527166 B1 04-03-2003
			ZA 200104595 A 05-09-2002
WO 9965796	A	23-12-1999	DE 19858781 A1 23-12-1999
			AU 4371999 A 05-01-2000
			BR 9912165 A 10-04-2001
			CN 1131827 B 24-12-2003
			WO 9965796 A1 23-12-1999
			EP 1086029 A1 28-03-2001
			ID 28157 A 10-05-2001
			JP 2002526333 T 20-08-2002
			PL 345003 A1 19-11-2001
			US 2002179464 A1 05-12-2002
			US 6457580 B1 01-10-2002
WO 03078274	A	25-09-2003	WO 03078274 A1 25-09-2003
US 6435342	B1	20-08-2002	AT 223338 T 15-09-2002
			AU 743375 B2 24-01-2002
			AU 3429799 A 01-11-1999
			BR 9909602 A 21-11-2000
			CA 2327292 A1 21-10-1999
			CN 1107002 B 30-04-2003
			CZ 20003680 A3 12-12-2001
			DE 69902771 D1 10-10-2002
			DK 1073595 T3 14-10-2002
			EA 2233 B1 28-02-2002
			EG 21448 A 31-10-2001
			EP 1073595 A1 07-02-2001

INTERNATIONAL SEARCH REPORT

Information on patent family members

International

Location No

PCT/IT 03/00572

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
US 6435342	B1	ES 2178418 T3	16-12-2002
		WO 9952791 A1	21-10-1999
		HK 1034234 A1	03-01-2003
		HU 0103095 A2	28-12-2001
		ID 27607 A	12-04-2001
		JP 2003516276 T	13-05-2003
		NO 20005049 A	04-12-2000
		NZ 507783 A	26-11-2002
		PL 343364 A1	13-08-2001
		PT 1073595 T	31-01-2003
		SI 1073595 T1	31-12-2002
		ZA 200005449 A	10-08-2001
FR 2499947	A	20-08-1982	
		DE 8104045 U1	02-07-1981
		BE 892125 A1	27-05-1982
		FR 2499947 A3	20-08-1982
		IT 1149645 B	03-12-1986
		LU 83944 A1	07-07-1982
		NL 8200543 A , B,	01-09-1982
FR 2495114	A	04-06-1982	
		FR 2495114 A1	04-06-1982
		FR 2496061 A2	18-06-1982